



**3 Type**

- A** Mounting from the back (threaded blind bore)
- B** Mounting from the operator's side (only for  $b_1=26$ )

Type A



Type B



**1**

**2**

$b_1$	Length $l$ $\pm 0,25$	$a$	$b_2$	$b_3$	$b_4$	$b_5 + 1$	$d_1$	$d_2$	$h_1$	$h_2$	$r$	$t$ min.
20	112	13	24	32	50	13,5	M 6	-	32	48	13	10
20	128	13	24	32	50	13,5	M 6	-	32	48	13	10
26	128	17	32	34	57	18	M 8	M 6	34	54	17	12
26	160	17	32	34	57	18	M 8	M 6	34	54	17	12

**Specification**

- Aluminum
  - Powder coated
    - Black, RAL 9005, textured finish
    - Silver, RAL 9006, textured finish
  - Anodized, natural color
  - Plain, tumbled
- Type B
  - Socket button head screws ISO 7380-M6-25
  - Hexagon nuts ISO 4032-M6
  - Washers DIN 125
- Steel, zinc plated, blue passivated
- Load Rating Information → Page 2106
- RoHS

- **SW**
- **SR**
- **EL**
- **BL**

**4**

**Information**

Inclined cabinet U-handles GN 565.2 are manufactured from a bent aluminum profile. Their special features are their rigidity and ergonomic shaping.

The angled contact surface allows improved access even in tight spaces such as corners.

Due to the manufacturing process, **special designs** can be supplied even in relatively small quantities.

For type B, socket button head screws, hexagon nuts and washers are included parts of the order.

see also...

- Product Family Standard Parts for Profile Systems → Page 18
- Cabinet U-Handles GN 425.1 (Angled) → Page 152 / 153
- Cabinet U-Handles GN 426.1 (Aluminum, Angled) → Page 158
- Cabinet U-Handles GN 630.1 (Plastic) → Page 116
- Assembly Sets for Profile Systems 30 / 40 GN 965 → Page 2086
- Assembly sets for Profile Systems 30 / 40 / 45 GN 968 → Page 2096

How to order	
<b>1</b>	$b_1$
<b>2</b>	Length $l$
<b>3</b>	Type
<b>4</b>	Finish

**GN 565.2-26-128-B-SW**