



No.04 : H30 Mesh size 38X38

	Bar thickness (Top/Bottom)	6.5/5.0
	Distance between centers of bearing bars	38
	Open Area	68%
	Weight per square meter	14.6 kg/m ²
Standard panel sizes: 1220x4000, 1220x3660, 1220x2440, 915x3050, Both directions		

Deflection	kg/m						Break point
	75	150	300	450	750	1500	
SPAN 300	<0.254	<0.254	0.254	0.508	0.762	1.524	9923.4
450	0.254	0.508	1.016	1.524	2.54	----	4827.6
600	0.508	1.27	2.286	3.556	5.842	----	4112.4
750	1.27	2.54	4.826	7.366	12.446	----	3173.7
900	1.778	3.81	7.62	11.43	----	----	2637.3

	Bar thickness (Top/Bottom)	7.0/5.0
	Distance between centers of bearing bars	38
	Open Area	68%
	Weight per square meter	19.5 kg/m ²
Standard panel sizes: 1220x4000, 1220x3660, 1220x2440, 915x3050, 1524x3050, 1524x4000, Both directions		

Deflection	kg/m						Break point
	75	150	300	450	600	750	
SPAN 300	0.279	0.356	0.483	0.61	0.762	0.889	17116
600	0.356	0.66	1.245	1.85	2.464	3.073	8718
900	0.864	1.803	3.683	5.563	7.417	9.296	5817
1200	2.26	4.749	9.677	14.63	19.583	----	3755